




Locking Devices – Shrink Discs – Locking Elements

Whatever has to be fixed to a shaft – we do have the perfect component. Regardless of whether the connection has to be inside, from the side or outside, in our portfolio you will find a wide range of variants for each individual application. Easy and quick assembly as well as high availability at reasonable prices are good reasons for the use of locking devices, shrink discs or locking elements by KBK compared to other solutions like the connection by keyways. All products can be obtained optionally chemically nickel plated or in stainless steel version. Upon request, the use of special stainless steels, like AISI 304 or AISI 316, is possible.

KBS10





- ▶ Locking device
- ▶ Shaft diameter: 45 - 390 mm
- ▶ Torque range: 3140 - 249000Nm

[more details](#)

IZDC11



[Search](#)

[Language](#)

[Menu](#)



- ▶ Locking device
- ▶ Shaft diameter: 25 - 375mm
- ▶ Torque range: 840 - 428000Nm

[more details](#)

KBS13





- ▶ Locking device
- ▶ Shaft diameter: 18 - 235mm
- ▶ Torque range: 310 - 46980Nm

[more details](#)

KBS15



- ▶ Locking device
- ▶ Shaft diameter: 14 - 80mm
- ▶ Torque range: 290 - 1780Nm

[more details](#)



KBK16

KBS 10



- ▶ Locking device
- ▶ Shaft diameter: 18- 235mm
- ▶ Torque range: 260 - 36100Nm

[more details](#)

KBS18



- ▶ Locking device
- ▶ Shaft diameter: 70 - 495mm
- ▶ Torque range: 7300 - 610000Nm

[more details](#)

KBS19



- ▶ Shrink disc
- ▶ Hollow diameter: 14 - 280mm
- ▶ Shaft diameter: 40 - 327000Nm

[more details](#)

KBS19/1



- ▶ Shrink disc
- ▶ Hollow diameter: 24 - 130mm

Torque range: 172 - 15300Nm

[more details](#)

KBS40



- ▶ Locking device
- ▶ Shaft diameter: 19 - 285mm
- ▶ Torque range: 255 - 68000Nm

[more details](#)

KBS50



locking element

- ▶ Shaft diameter: 6 - 244mm
- ▶ Torque range: 2,4 - 38100Nm

[more details](#)

KBS51



- ▶ Locking device
- ▶ Shaft diameter: 14 - 84mm
- ▶ Torque range: 52 - 1433Nm

[more details](#)

KBS52



locking device

- ▶ Shaft diameter: 16 - 148mm
- ▶ Torque range: 82 - 9231Nm

[more details](#)

KBS55



- ▶ Locking device
- ▶ Shaft diameter: 14 - 79mm
- ▶ Torque range: 65 - 1200Nm

[more details](#)

KBS56





- ▶ Locking device
- ▶ Shaft diameter: 5 - 45mm
- ▶ Torque range: 11 - 390Nm

[more details](#)

KBS57



- ▶ Locking device
- ▶ Shaft diameter: 4 - 50mm
- ▶ Torque range: 3 - 95Nm

[more details](#)

KBS58





- ▶ Locking device
- ▶ Shaft diameter: 5 - 75mm
- ▶ Torque range: 10 - 2320Nm

[more details](#)

KBS59



- ▶ Locking device
- ▶ Shaft diameter: 5 - 60mm
- ▶ Torque range: 10 - 1340Nm

[more details](#)

KBS61





- ▶ Locking device
- ▶ Shaft diameter: 5 - 80mm
- ▶ Torque range: 6 - 1900Nm

[more details](#)

KBS62



- ▶ Locking device
- ▶ Shaft diameter: 30 - 465mm
- ▶ Torque range: 620 - 543000Nm

[more details](#)



KBS70



- ▶ Locking device
- ▶ Shaft diameter: 19 - 235mm
- ▶ Torque range: 350 - 41300Nm

[more details](#)

KBS71



- ▶ Locking device
- ▶ Shaft diameter: 19 - 235mm
- ▶ Torque range: 300 - 34250Nm

[more details](#)

KBS80



- ▶ Locking device
- ▶ Shaft diameter: 6 - 155mm
- ▶ Torque range: 12 - 17500Nm

[more details](#)

KBS95



- ▶ Rigid shaft coupling
- ▶ Shaft diameter: 15 - 125mm
- ▶ Torque range: 158 - 4300Nm



[more details](#)

Company

[About us](#)[News](#)[Contact person](#)[Representations](#)[Certificate](#)

Products

[Metal Bellows Couplings](#)[Servo Insert Couplings](#)[Cardan Couplings](#)[Line Shafts](#)[Rigid shaft couplings](#)[Locking Devices / Shrink Discs](#)[Safety Couplings](#)[Magnetic Couplings](#)[Measuring Gearbox](#)

Infos

[Downloads](#)[Contact](#)[print](#)[General business terms](#)

General business terms

Data protection

KBK Antriebstechnik GmbH

Unterlandstrasse 46

63911 Klingenberg am Main

Phone.: +49-9372-94061-0

Fax: +49-9372-94061-29

info(at)kbk-antriebstechnik.de

